

Connectable cable area and torques on products with terminal connection made by EI-Björn AB

*Anslutningsbar kabelarea och åtdragningsmoment
på produkter med plintanslutning tillverkade av EI-Björn AB*

Type <i>Typbeteckning</i>	Connectable area [mm] <i>Anslutningsbar area</i>	Torque <i>Åtdragningsmoment</i>
SF 100//114-1	Al/Cu 10-95	15 Nm
SF 100//114-12	Al/Cu 10-95	15 Nm
SF 100//006	Al/Cu 10-95	15 Nm
SF 100//006-03	Al/Cu 10-95	15 Nm
SF 100//3321-2	Cu 1x35-70 / 2x16-70 Al 1x35-120 / 2x16-120	Cu 35-95mm ² 20Nm Cu 120-240mm ² 45Nm Al 35-240mm ² 20Nm
SF 100//3321-22	Cu 1x35-70 / 2x16-70 Al 1x35-120 / 2x16-120	Cu 35-95mm ² 20Nm Cu 120-240mm ² 45Nm Al 35-240mm ² 20Nm
SF 125//3122-1	Cu 1x35-70 / 2x16-70 Al 1x35-120 / 2x16-120	Cu 35-95mm ² 20Nm Cu 120-240mm ² 45Nm Al 35-240mm ² 20Nm
SF 125//3122-13	Cu 1x35-70 / 2x16-70 Al 1x35-120 / 2x16-120	Cu 35-95mm ² 20Nm Cu 120-240mm ² 45Nm Al 35-240mm ² 20Nm
ZSF 25//311-1	Al/Cu 2,5-50	10 Nm
ZSF 25//311-11	Al/Cu 2,5-50	10 Nm
ZSF 63//1111-1	Al/Cu 16-95	14 Nm
ZSF 63//1111-11	Al/Cu 16-95	14 Nm
ZSF 63//3321-2	Al/Cu 16-95	14 Nm
ZSF 63//3321-21	Al/Cu 16-95	14 Nm
ZSF 100/1/3322-2	Al/Cu 10-95	15 Nm
ZSF 100/1/3322-23	Al/Cu 10-95	15 Nm
ZSF 125/1/3111-1	Al/Cu 10-95	15 Nm
ZSF 125/1/3111-12	Al/Cu 10-95	15 Nm
ZFSF 160/1/3322-2	Al/Cu 95-240 Al/Cu 10-95	25 Nm 15 Nm
ZFSF 160/1/3322-23	Al/Cu 95-240 Al/Cu 10-95	25 Nm 15 Nm
FSF 160/1/3322-2	Al/Cu 95-240 Al/Cu 10-95	25 Nm 15 Nm
FSF 160/1/3322-23	Al/Cu 95-240 Al/Cu 10-95	25 Nm 15 Nm
FUC 63//3321-2	Al/Cu 2x16-95	14 Nm
FUC 63//3321-21	Al/Cu 2x16-95	14 Nm